

Ainulaadse disainiga seinamudel

FTXA-AW/S/T Stylish

(-10 °C/ -15 °C)

- Saadaval kolme erinevate värvitoonidega: valge, hõbedane ja puitimitatsioon
- Coanda efektiga optimeeritud õhuvool
- Mitmetsooniline ruumi temperatuuri jälgiv silm
- Madal müratase 19 dB(A)
- Integreeritud WiFi kontrollor
- Energiaklass jahutus/küte = A+++ / A+++
- R32 külmaaine



Mudel	Siseosa (valge)		FTXA20AW	FTXA25AW	FTXA35AW	FTXA42AW	FTXA50AW	
	Siseosa (hõbedane)		FTXA20AS	FTXA25AS	FTXA35AS	FTXA42AS	FTXA50AS	
	Siseosa (puit)		FTXA20AT	FTXA25AT	FTXA35AT	FTXA42AT	FTXA50AT	
	Välisosa		RXA20A	RXA25A	RXA35A	RXA42A	RXA50A	
Jahutusvõimsus	Min./Nom./Max	kW	1.3/2.0/2.6	1.3/2.5/3.2	1.4/3.4/4.0	1.7/4.2/5.0	1.7/5.0/5.3	
Küttevõimsus	Min./Nom./Max	kW	1.3/2.5/3.5	1.3/2.8/4.7	1.4/4.0/5.2	1.7/5.4/6.0	1.7/5.8/6.5	
Elektri tarbimine	Jahutus	Nom.	kW	0,43	0,56	0,78	1,05	1,36
	Küte	Nom.	kW	0,50	0,56	0,99	1,31	1,45
Aastane energiakulu (jahutus)		kWh	80	101	137	196	239	
SEER (jahutus)			8,53	8,74	8,73	7,5	7,33	
Aastane energiakulu (küte)		kWh	653	666	680	1150	1217	
SCOP			5,15			4,6		
Energiaklass	Jahutus		A+++			A++		
	Küte		A+++			A++		
Siseosa õhu hulk	Jahutus min/maks.	m ³ /h	276/660	276/690	276/714	276/786	312/810	
	Küte min/maks.	m ³ /h	270/654	270/666	276/690	312/876	342/906	
Müratase	Siseosa Jahutus	dB(A)	19/25/32/39	19/25/33/40	19/25/33/41	21/29/37/45	24/31/42/46	
	Siseosa Küte	dB(A)	19/25/32/39	19/25/33/40	19/25/33/41	21/29/37/45	24/33/42/46	
	Välisosa Jahutus	dB(A)	46		49	48		
Mõõdud (KxLxS)	Siseosa	mm	295x798x189					
	Välisosa	mm	550x765x285		735x825x300			
Kaal (netto)	Siseosa	kg	12,0			47		
	Välisosa	kg	32			47		
Torustiku mõõt	Vedel + Gaas	mm	6.35 + 9.5		6.35 + 12.7			
Freoon			R-32					
Maksimaalne trassi pikkus		m	20			30		
Maksimaalne kõrguste vahe		m	15			20		
Lubatud tööpiirid		Jahutus/Küte	°C				-10 ÷ 46/ -15 ÷ 18	
Elektriandmed		Pinge	V/Ph/Hz				220-240/1/50	