

Wall mounted unit

FTXTA-BB + RXTA-B



BLUEEVOLUTION stylish



Guaranteed operation down to -25°C



Fireplace logic



Coanda effect - heating



Heat boost



Daikin Residential Controller

Where innovation meets creativity, even at ambient temperatures down to -25°C

- › Guaranteed heating capacity down to -25°C
- › Even temperature distribution thanks to fireplace logic
- › Compact design in matt black
- › Perfect temperature distribution thanks to Coanda effect
- › Intelligent thermal sensor: air flow is adjusted when detecting temperature differences
- › Daikin residential controller via app
- › Voice control

- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A+++ in cooling and heating
- › Daikin Flash Streamer technology: powerful air purification
- › Practically inaudible
- › Heat boost: fast heating during start-up (pair only)

FTXTA-BB + RXTA-B



Indoor unit		FTXTA		30BB	
Dimensions	Unit	HeightxWidthxD	mm	295 x798 x189	
Weight	Unit			11.5	
Air filter	Type			Removable / washable	
Fan	Air flow rate	Cooling	Silent operation/Low/ Medium/High	m ³ /min	
		Heating	Silent operation / Low / Medium / High	m ³ /min	
Sound power level	Cooling			60	
	Heating			60	
Sound pressure level	Cooling	Silent operation/Low/High		20 /25 /43	
	Heating	Silent operation/Low/High		19 /24 /41	
Control systems	Infrared remote control		ARC466A59		
	Wired remote control		BRC073A4		

Cooling: indoor temp. 27°CDB, 19.0°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data


Outdoor unit		RXTA		30B	
Dimensions	Unit	HeightxWidthxD	mm	551 x763 x312	
Weight	Unit			38	
Sound power level	Cooling			61	
Sound pressure level	Cooling	Nom.		48	
	Heating	Nom.		49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	
	Heating	Ambient	Min.~Max.	°CWB	
Refrigerant	Type			R-32	
	GWP			675	
	Charge	kg/TCO ₂ Eq		1.1 /-	
Piping connections	Liquid	OD	mm	6.35	
	Gas	OD	mm	9.50	
	Piping length	OU - IU	Max.	m	
	Additional refrigerant charge			kg/m	
	Level difference	IU - OU	Max.	m	
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50 /220-240
Current - 50Hz	Maximum fuse amps (MFA)		A		16

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data		FTXTA + RXTA		30BB + 30B	
Cooling capacity	Min./Nom./Max.	kW		0.70 /3.00 /4.50	
Heating capacity	Min./Nom./Max.	kW		0.80 /3.20 /6.90	
Power input	Cooling	Nom.		kW	
	Heating	Nom.		kW	
Space cooling	Energy efficiency class		A++		
	Capacity	Pdesign	kW		3.00
	SEER			7.63	
	Annual energy consumption			kWh/a	
Space heating (Average climate)	Energy efficiency class		A+++		
	Capacity	Pdesign	kW		2.60
	SCOP/A			5.10	
	Annual energy consumption			kWh/a	
Space heating (Cold climate)	Energy efficiency class		A+		
	Capacity	Pdesignh	kW		3.80
	Annual energy consumption			kWh/a	
	SCOP/C			4.10	
Nominal efficiency	EER			4.20	
	COP			4.87	
	Annual energy consumption	kWh		357	
	Energy labeling Directive	Cooling/Heating		A/A	

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range

Daikin Europe N.V. Naamloze Venootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN21-063

06/2021



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.